

What is claimed:

1. A wavelength division multiplexing optical communication system for transmitting wavelength division multiplexed signal light containing a plurality of optical signals of different wavelengths, from a transmitting terminal station to a receiving terminal station via an optical transmission path, wherein

said receiving terminal station comprises reception characteristics measurement means for measuring reception information including optical signal to noise ratio and a transmission error rate for the optical signals of respective wavelengths transmitted through said optical transmission path, and reception information transmission means for transmitting the reception information about each wavelength measured by said reception characteristics measurement means to said transmitting terminal station, and

said transmitting terminal station comprises pre-emphasis performing means for performing pre-emphasis on the wavelength division multiplexed signal light transmitted along said optical transmission path, chirp applying means for applying an optical wavelength chirp to the wavelength division multiplexed signal light transmitted along said optical transmission path, and control means for controlling, depending on the reception information about each wavelength transmitted from said receiving terminal station, the setting of pre-emphasis in said pre-emphasis performing device, and the setting of a parameter α representing an amount of the optical wavelength chirp in said chirp applying means.

2. A wavelength division multiplexing optical communication system according to claim 1, wherein

said optical transmission path has a first line for transmitting wavelength division multiplexed signal light from said transmitting terminal station to said receiving terminal station, and a second line opposite to said first line, and

said reception information transmission means superimposes the reception information about each wavelength measured by said reception characteristics measuring means, onto overhead information of the optical signals corresponding to respective wavelength which is transmitted along said second line, and transmits this to said transmitting terminal station end.

3. A wavelength division multiplexing optical communication system according to claim 1, wherein

09775530, 020604

Sub 1

said transmitting terminal station comprises: optical transmitting device for generating said optical signals of respective wavelength and outputting these, optical multiplexing device for multiplexing the optical signals of respective wavelengths output from said optical transmitting device and outputting to said optical transmission path, and reception information transfer means for transferring the reception information about each wavelength transmitted from said receiving terminal station between said optical signal transmitting device and said optical multiplexing device, and said pre-emphasis performing means and said chirp applying means are respectively provided in at least one of said optical signal transmitting device and said optical multiplexing device.

4. A wavelength division multiplexing optical communication system according to claim 3, wherein there is provided an optical amplifier disposed on said optical transmission path, and

said transmitting terminal station has reception information transmitting means for transmitting the reception information about each wavelength transmitted from said receiving terminal station to said optical amplifier, and

said optical amplifier has supervisory control means for controlling operating conditions in accordance with the reception information about each wavelength transmitted from said transmitting terminal station.

5. A wavelength division multiplexing optical communication system according to claim 3, wherein there is provided an optical add and drop multiplexer disposed on said optical transmission path, and

said transmitting terminal station has reception information transmitting means for transmitting the reception information about each wavelength transmitted from said receiving terminal station to said optical add and drop multiplexer, and

said optical add and drop multiplexer has supervisory control means for controlling operating conditions in accordance with the reception information about each wavelength transmitted from said transmitting terminal station.

6. A wavelength division multiplexing optical communication system according to claim 1, wherein

said transmitting terminal station has wavelength dispersion compensating means for compensating for wavelength dispersion characteristics of said optical transmission path, and said control means also controls a wavelength dispersion

09775630.020604

compensation amount in said wavelength dispersion compensation means corresponding to the reception information about each wavelength transmitted from said receiving terminal station.

7. A wavelength division multiplexing optical communication system according to claim 1, wherein

said receiving terminal station comprises: wavelength dispersion compensating means for compensating for wavelength dispersion characteristics of said optical transmission path, polarization-mode dispersion compensating means for compensating for polarization-mode dispersion generated in said optical transmission path, data discriminating means for performing data discrimination processing of received wavelength division multiplexed signal light, and control means for respectively controlling a wavelength dispersion compensation amount in said wavelength dispersion compensation means, a polarization-mode dispersion compensating amount in said polarization-mode dispersion compensating means and the setting of a discrimination decision point in said data discriminating means, depending on the reception information about each wavelength transmitted from said receiving terminal station.

8. A wavelength division multiplexing optical communication system according to claim 1, wherein said reception characteristics measurement means measures an electrical signal to noise ratio pertaining to the optical signals of respective wavelengths transmitted along said optical transmission path, and converts the measured electrical signal to noise ratio to an optical signal to noise ratio according to a previously set relationship between the electrical signal to noise ratio and the optical signal to noise ratio, to thereby obtain reception information about each wavelength.

9. A wavelength division multiplexing optical communication system according to claim 1, wherein said reception characteristics measurement means measures an electrical signal to noise ratio pertaining to the optical signals of respective wavelengths transmitted along said optical transmission path, and converts the measured electrical signal to noise ratio to the transmission error rate according to a previously set relationship between the electrical signal to noise ratio and the transmission error rate, to thereby obtain reception information about each wavelength.

in said receiving terminal station, reception information including an optical signal to noise ratio and a transmission error rate for the optical signals of respective wavelengths transmitted through said optical transmission path is measured, and the measured reception information about each wavelength is transmitted to said transmitting terminal station, and

11. A wavelength division multiplexing communication system for transmitting wavelength division multiplexed signal light containing a plurality of optical signals of different wavelengths, from a transmitting terminal station to a receiving terminal station via an optical transmission path and an optical repeater station, wherein

said transmitting terminal station comprises pre-emphasis performing means for performing pre-emphasis on the wavelength division multiplexed signal light transmitted along said optical transmission path, control means for controlling, depending on the reception information about each wavelength transmitted from said receiving terminal station, the setting of pre-emphasis in said pre-emphasis performing means, and reception information transfer means for transferring the reception information about each wavelength transmitted from said receiving terminal station to said optical repeater station, and

12. A wavelength division multiplexing optical communication system according to claim 11, wherein

13. A wavelength division multiplexing optical communication system according to claim 11, wherein

said reception information transfer means of said receiving terminal station superimposes the reception information about each wavelength measured by said reception characteristic measuring means, onto overhead information of the optical signals corresponding to said wavelengths which is transmitted by said second line, and transmits this to said transmitting terminal station end, and

14. A wavelength division multiplexing optical communication system according to claim 11, wherein

said reception information transmission means of said receiving terminal station comprises a function for transmitting the reception information about each wavelength measured by said reception characteristics measuring means to said optical repeater station, instead of the reception information transfer means of said transmitting terminal station.

15. A wavelength division multiplexing optical communication system according to claim 11, wherein

when a plurality of optical repeater stations are arranged on said transmission path, the supply condition of Raman excitation light in said Raman amplifier by said Raman amplifier control means is controlled only for a specific optical repeater station selected from said plurality of optical repeater stations.

16. A wavelength division multiplexing optical communication method for transmitting a wavelength division multiplexed optical signal containing a plurality of optical signals with different wavelengths, from a transmitting terminal station to a receiving terminal station via an optical transmission path and an optical repeater station, wherein

in said receiving terminal station, reception information including an optical signal to noise ratio and a transmission error rate for the optical signals of respective wavelengths transmitted through said optical transmission path is measured, and the measured reception information about each wavelength is transmitted to said transmitting terminal station,

in said transmitting terminal station, depending on the reception information about each wavelength transmitted from said receiving terminal station, the setting of pre-emphasis to be performed on the wavelength division multiplexed signal light transmitted along said optical transmission path is controlled, and the reception information about each wavelength transmitted from said receiving terminal station is transferred to said optical repeater station, and

in said optical repeater station, depending on the reception information about each wavelength transmitted from said transmitting terminal station, a supply condition of Raman excitation light for Raman amplifying the wavelength division multiplexed signal light transmitted through said optical transmission path is controlled.

17. A wavelength division multiplexing optical communication system for transmitting a wavelength division multiplexed optical signal containing a plurality of optical signals with different wavelengths, from a transmitting terminal station to a receiving terminal station via an optical transmission path and an optical repeater station, wherein

said receiving terminal station comprises reception characteristics measurement means for measuring reception information including an optical signal to noise ratio and a transmission error rate for the optical signals of respective

00776630-020604

said optical repeater station comprises optical amplification means containing a Raman amplifier for Raman amplifying the wavelength division multiplexed signal light transmitted from said optical transmission path, and Raman amplification control means for controlling a supply condition of Raman excitation light in said Raman amplifier corresponding to the reception information about each wavelength transmitted from said transmitting terminal station.

Add 7